


WASHER LOCATION DETAIL

NOTE: FOR 'T'-BEAM GUARDRAIL, WASHER IS PLACED IN THE TOP INDENTION.

\* WHERE BOLT DOES NOT EXTEND
THRU RAIL REFLECTORIZED
WASHER IS ATTACHED UNDER THE
SPLICE BOLT ON THE TOP CORRUGATION,
IF REQUIRED.



TYPICAL GUARDRAIL INSTALLATION

BRIDGE END OR CONC. BARRIER

TRAFFIC FLOW

TRAILING END-BRIDGE OR CONCRETE BARRIER

## SPACING OF REFLECTORIZED WASHERS

AT ANCHORAGES:

-TWO (2) REFLECTORIZES WASHERS ARE REQUIRED ON THE RAIL UNDER SPLICE BOLTS AS DIRECTED BY THE ENGINEER FOR ELLIPTICALLY FLARED ANCHORAGES WITH ROUNDED END PIECES;

-NO REFLECTORIZED WASHERS WILL BE USED FOR TANGENTIALLY ALIGNED OR STRAIGHT TAPERED ANCHORAGE WITH EXTRUDER OR IMPACT HEADS

- B) -AT 75 FT. SPACINGS FOR INTERMEDIATE SECTIONS;
- C) -THREE WASHERS AT 6'-3" SPACING AT CONNECTIONS TO CONCRETE FACE ON THE APPROACH END;

9.76720.06 □ 527.27 ¬AM \\GDPI OT\OCF\aa TIFF autout.acf aowens M:\GARY\RFVISFO 4360\4360.aff

-AT 12'-6" SPACINGS AROUND RADII TURNS.

## GENERAL NOTES:

- I-SPECIFICATIONS: GEORGIA STANDARD, CURRENT EDITION, & SUPPLEMENTS THERETO.
- 2-SEE SEPARATE STANDARDS FOR DETAILS OF GUARDRAIL INSTALLATIONS, CONNECTING HARDWARE, AND ANCHORAGES.
- 3-PAYMENT FOR GUARDRAIL AND ANCHORAGES INCLUDES ALL REFLECTORIZED WASHERS AND NOSE STRIPING REQUIRED.
- 4-ADJUSTMENTS OF SPACINGS AND/OR REQUIREMENTS FOR REFLECTIVE WASHERS MAY BE DIRECTED BY THE ENGINEER TO SUIT INDIVIDUAL LOCATIONS.
- 5-WHERE DOUBLE FACED GUARDRAIL IS LOCATED ON THE INSIDE SHOULDER OF MEDIANS, REFLECTORIZED WASHERS SHALL BE REQUIRED ONLY ON THE SIDE WHICH IS NEAREST TO TRAFFIC, UNLESS SPECIFIED OTHERWISE.

	4-10-06	6-1-9	DATE	DEP	ARTMENT OF TRANSPORTATION STATE OF GEORGIA
	YPE.		·		STANDARD
	REFLECTIVE, SH. 1	STF	REVISION		REFLECTORIZED GUARDRAIL WASHERS AND ANCHORAGE NOSE STRIPING
	REV. REFI	ADD N		NO SCALE	REV. & REDR. APRIL, 1999
	CL0	RMU	ВҮ	DES DRWN CHK	(SUBMITTED) BASSIGN ENGINEER STATE ROAD & AIRPORT DESIGN ENGINEER 4360